ASSEMBLY INSTRUCTIONS


ITEM NO:B2-201-26L/B2-201-30L

Don't tighten any Bolts until all Bolts on a step have been started

Thank you for pur chasing this quality product. Be sure to check all packing material carefully for small parts, which may have come loose inside the carton during shipment. I dentify and count all parts and compare with the HARDWARE LIST below.


| NO | PARTS LIST | | PARTS NO, | Q'TY |
|----|------------|---------------------|-----------------------------|----------|
| Α | 0 | Bonded leather seat | B2201-26LP1 | 1 |
| В | 0 | Top ring | B2201-26LP2 | 1 |
| С | ® | Metal swivel | B2200-26LP3 | 1 |
| | | Middle ring | B2201-26LP4 | pro-assy |
| D | 0 | Bottom ring | B2201-26LP5 | 1 |
| E | | Leg | B2201-26LP6/ B2201-30LP6 | 4 |
| F | | Stool back | B2201-26LP8 | 1 |

| NO. | PARTS LIST | | PARTS NO. | Q'TY |
|-----|-------------------|--------------|-------------|------|
| 1 | ap) •• | 1/4"*2" | | 8 |
| 2 | 6)- | 1/4"*1 3/4" | | 6 |
| 3 | 3 | 1/4"*1" | B2201-26LP7 | 4 |
| 4 | €9>= | 1/4"*2 1/4" | | 4 |
| 5 | Викимини - | 8*1 1/2" | | 4 |
| 6 | _ | Allen Wrench | | 1 |




- 1. Attach the Bonded leather seat(A) to the Top RING(B), using Screws(5) to tighten, as shown.

 2. Attach the stool back(F) to the (A+B) using Bolts(2)(4) to tighten,
- as shown.




- 1.Attach the four Legs(E)to the Middle Ring(C),using Bolts(1) to tighten, as shown
- 2. Attach the Bottom Ring(D) to the Legs, using Bolts (2) to tighten, as shown.





- 1. Upside down the Wooden Seat Back(STEP1) and put it on a smooth and stable working stand.
- 2.Attach the Stool Base(STEP2)to the Seat w/pre-assembly Seat Back(STEP1), using Bolls(3) to tighten, as shown.

STEP 4



1. It's complete for using,