OFRAN INC.

ASSEMBLY INSTRUCTIONS & PARTS IDENTIFICATION

MODEL # 1885

5 PACK TABLE & CHAIRS

5-Pack Hardware Kit (1885PO1) Table Hardware

Table Haruware					
Ltr	Qty	Description			
A	8 pcs	Flat Washer			
В	8 pcs	Lock Washer			
\mathbf{C}	8 pcs	Nut 5/16"			
D	1 pc	Key Wrench			






Table Parts Key						
No			Description			
1	1885P01FT	4 pcs.	TableFloor Glide Leg Table top			
2		4 pcs.	Leg			
3		1 pc.	Table top			





Detail A

-Carefully lay table top upside down on a smooth flat surface to prevent scratches.


-Affix a leg to each corner of the table top as shown in Detail A using a flat washer, lock washer and nut.

-Once all legs are in place, fully tighten the nuts


5-Pack Hardware Kit (1885P46) **Chair Hardware**

Ltr	Qty	Description
A	44 pcs.	Flat Washer 5/16"
В	44 pcs.	Lock Washer 5/16"
C	16 pcs.	Nut 5/16"
D	1 pc.	Key Wrench
E	16 pcs.	Long KD. Bolt 1/4"x 3".
F	12 pcs.	Short KD. Bolt 1/4"x 1.5".
G	1 pc.	Allen Wrench

Chair Parts Key						
No	Code	Qty	Description			
5	1885P01F0	16 pcs.	Chair Floor Glide			
6		4 pcs.	Chair Back			
7	1885P41	4 pcs.	Complete Seat			
8	1885P42	8 pcs.	Front Leg			



* Quantities noted are for a tolal of four chairs.




FABRIC CARE INSTRUCTION REGULAR CARE: Clean with shampoo, foam, or dry cleaning solvents as desired. Do not

STEP 2

- saturate with liquid. Pile fabrics may require brushing to restore FABRIC CONTENT 100% Polyester; Cleaning code "WS"
- Carefully turn chair upside down and affix each Leg to the front corner of the complete seat, as shown in Detall C, using a flat washer, lock washer, and nut.
- Turn chair upright and make sure it is level before fully tightening all bolts and nuts.
- Be sure to tighten all screws prior to using chair.

STEP 1

- Carefully lay chair back flat on a smooth flat surface to prevent scratches.
- Affix the complete seat to chair back, as shown in Detall A, using a flat washer, lock washer and short KD bolt.
- Secure complete seat to chair back corners, as shown in Detail B, using a flat washer, lock washer and long KD bolt. - - Tighten screws with provided Allen Wrench.



STEP 1